

Declaration of Performance according to Regulation (EU) 305/2011

No. 00019-CPR-2014/08/08

1) Unique identification code of the product-type:

Roomheater burning solid fuel *with* hot water supply EN 13229:2001/A2:2004

2) Type, batch or serial number or any other element allowing identification of the construction product as required under Article 11 : “*Model Barun Insert Termo*”

Fireplace stoves burning wood made by PLAMEN d.o.o, are designed for heating and additional heating of residential and social rooms, i.e. standard environment without the explosion hazard and the presence of volatile substances. The fireplace stoves are designed for interrupted operation.

Basic technical parameters

Type	Main dimensions (mm)			Nominal power output (kW)	Fuel consumption - wood (kg/hour)	Diameter of the uptake (mm)	Operational draught (Pa)
	Width	Height	Depth				
Barun Insert Termo	690	590	440	7,5/7,5	5,2	180	12

3) Intended use or uses of the construction product, in accordance with the applicable harmonised technical specification, as foreseen by the manufacturer:

Roomheater burning solid fuel *with* hot water supply
Appliances are determined for intermittent operation.

4) Name, registered trade name or registered trade mark and contact address of the manufacturer as required pursuant Article 11 :

PLAMEN d.o.o.
Njemačka 36, 34000 Požega
Croatia

5) Where applicable, name and contact address of the authorised representative whose mandate covers the tasks specified in Article 12 : “*No representative appointed*”

6) System or systems of assessment and verification of constancy of performance of the construction product as set out in Annex V:

System 3 (Annex V, Clause 1.4 of Regulation 305/2011 of the European Parliament and of the Council of 9 March 2011)

7) The Declaration of Performance concerning a construction product covered by a harmonised standard:

(ČSN)EN 13229:2001 /A2:2004

The assessment acc. to System 3 has been carried out by Strojírenský zkušební ústav, s.p., Hudcova 424/56b, 621 00 Brno, Notified Body 1015, which issued the Report on Initial Type Testing 30-11685 of 2012-07-31.

8) Declared performance

Harmonized technical specification	EN 13229:2001/A2:2004
Essential characteristics	Performance
Fire safety	
Reaction to fire	A1
Distance to combustible materials	Minimum distances, in mm rear = sides = ceiling = front = 1200 floor =
Risk of burning fuel falling out	Pass
Emission of combustion products	CO[0.316 %]
Surface temperature	Pass
Electrical safety	Pass
Cleanability	Pass
Maximum operating pressure	-
Flue gas temperature at nominal heat output	T [360 °C]
Mechanical resistance (to carry a chimney/flue)	NPD
Thermal output	
Nominal heat output	15/7,5 kW
Room heating output	15,87 kW
Water heating output	-
Energy efficiency	[70,08 %] η

9) The performance of the product identified in points 1 and 2 is in conformity with the declared performance in point 8.

This Declaration of Performance is issued under the sole responsibility of the manufacturer identified in point 4.

Signed for and on behalf of the manufacturer by:

Igor Ujaković, head of product development

.....
(name and function)

Požega, 08.08.2014

.....
(place and date of issue) (signature)