

**DECLARATION OF PERFORMANCE
according to Regulation (EC) 305/2011
No. 2010 - 003 – 0001**

- | | | |
|--------------------------|---|--|
| 1 | Unique identification code of the product-type: | Room heaters fired by wood fuel without hot water supply
DIANA |
| 2. | Type, batch or serial number or any other element allowing identification of the construction product as required under Article 11(4): | Serial No (see rating label on the product): 00001 |
| 3. | Intended use or use of the construction product, in accordance with the applicable harmonized technical specification, as foreseen by the manufacturer: | Appliance with intermittent and continues burning regime for operation with closed doors |
| 4. | Name, registered trade name or registered trade mark and contact address of the manufacturer as required pursuant Article 11(5): | TIM SISTEM d.o.o.
Industrial area Nova Pazova
22 330 Nova Pazova, Serbia, e-mail: office@timsistem.rs |
| 5. | Where applicable, name and contact address of the authorized representative whose mandate covers the tasks specified in Article 12 (2): | - |
| 6. | System or systems of assessment and verification of constancy of performance of the construction product as set out in Annex V: | System 3 |
| 7. | In case of the declaration of performance concerning a construction product covered by a harmonized standard: | TERMOLAB Ltd - Novi Iskar
18 Kesten str., 1280 Novi Iskar, Republic of Bulgaria
Body: NB2033
Test report:22/06.07.2010 |
| 8. Declared performance: | | |

Harmonized technical specification	EN 13240:2001/A2:2004/AC:2007
Essential characteristics	Performance
Fire safety	
Reaction to fire	A1
Distance to combustible materials	Minimum distance, in mm sides = 300, rear = 300, front = 800
Risk of burning fuel falling out	Pass
Emission of combustion products	CO [0,0808 %]
	Dust [68mg/Nm ³]
	NOx [- mg/Nm ³]
	CxHy [- mg/Nm ³]
Surface temperature	Pass (operating tool)
Electrical safety	NPD
Clean ability	Pass
Maximum water operating pressure	- bar
Flue gas temperature at nominal heat output	T [107,6 °C]
Mechanical resistance (to carry a chimney/flue)	NPD
Thermal output	
Nominal heat output	10 kW
Room heating output	10 kW
Water heating output	- kW
Energy efficiency	η [89%]

9. The performance of the product identified in points 1 and 2 is in conformity with the declared performance in point 8. This declaration of performance is issued under the sole responsibility of the manufacturer identified in point 4.

11.08.2010.




Ivan Stanković, CEO